


Application No.: 10/669,403
Docket No.: UC0315USNA

RECEIVED
CENTRAL FAX CENTER

SEP 5 - 2007

Listing of Claims

1. (Cancelled)
2. (Cancelled)
3. (Cancelled)
4. (Cancelled)
5. (Cancelled)
6. (Cancelled)
7. (Cancelled)
8. (Cancelled)
9. (Cancelled)
10. (Cancelled)
11. (Cancelled)
12. (Cancelled)
13. (Cancelled)
14. (Cancelled)
15. (Currently Amended) A liquid composition for depositing an active material selected from electrically active materials, photoactive materials, and mixtures of such materials, onto a surface, said composition comprising:
 - the active material; and
 - at least one ~~material~~ liquid medium selected from compounds having the structure



wherein:

R is C₁-C₁₀ alkyl, C₁-C₁₀ alkoxy, or C₁-C₁₀ oxyalkyl,

R_f is C₂-C₃ fluorinated alkyl, C₁-C₁₀ fluorinated alkenyl, C₁-C₁₀ fluorinated oxyalkyl, or C₁-C₁₀ fluorinated oxyalkenyl,

Application No.: 10/669,403

Docket No.: UC0315USNA

X is H, F, Cl, Br, C₁-C₁₀ alkyl, C₁-C₁₀ alkoxy C₁-C₁₀ oxyalkyl, C₁-C₁₀ fluorinated alkyl, C₁-C₁₀ fluorinated alkenyl, C₁-C₁₀ fluorinated oxyalkyl, or C₁-C₁₀ fluorinated oxyalkenyl,

m is from 0-5, and

n is from 0-5, wherein m + n is no greater than 5.

16. (Cancelled)

17. (Cancelled)

18. (Cancelled)

19. (Cancelled)


20. (Cancelled)

21. (Cancelled)


22. (Currently Amended) A liquid composition for depositing an active material selected from electrically active materials, photoactive materials, and mixtures of such materials, onto a surface, said composition comprising:

the active material; and


at least one liquid medium compound selected from compounds A through O and mixtures thereof:



A












B



C

Application No.: 10/669,403


Docket No.: UC0315USNA

**D****F****G****I****K****L****M****N****O**

23. (Currently Amended) A liquid composition for depositing an active material selected from electrically active materials, photoactive materials, and mixtures of such materials, onto a surface, said composition comprising:
the active material; and

Application No.: 10/669,403
 Docket No.: UC0315USNA

at least one ~~material~~ liquid medium selected from compounds having the structure



wherein:

R and X are each, independently, is C₁-C₁₀ alkyl, C₁-C₁₀ alkoxy, or C₁-C₁₀ oxyalkyl,

R_f is C₂-C₃ fluorinated alkyl, C₁-C₁₀ fluorinated alkenyl, C₁-C₁₀ fluorinated oxyalkyl, or C₁-C₁₀ fluorinated oxyalkenyl,

X is H, F, Cl, Br, C₁-C₁₀ alkyl, C₁-C₁₀ alkoxy, C₁-C₁₀ oxyalkyl, C₁-C₁₀ fluorinated alkyl, or C₁-C₁₀ fluorinated oxyalkyl,

m is from 0-5, and

n is from 0-5, wherein m + n is no greater than 5.

24. (New) A liquid composition of claim 15 capable of forming a static contact angle of no greater than 40 degrees on said surface.

25. (New) A liquid composition of claim 15 wherein the static contact angle is no more than 35 degrees.

26. (New) A liquid composition of claim 15 wherein the static contact angle is no more than 20 degrees.

27. (New) A liquid composition of claim 22 capable of forming a static contact angle of no greater than 40 degrees on said surface.

28. (New) A liquid composition of claim 22 wherein the static contact angle is no more than 35 degrees.

29. (New) A liquid composition of claim 22 wherein the static contact angle is no more than 20 degrees.

30. (New) A liquid composition of claim 23 capable of forming a static contact angle of no greater than 40 degrees on said surface.

Application No.: 10/669,403
Docket No.: UC0315USNA

31. (New) A liquid composition of claim 23 wherein the static contact angle is no more than 35 degrees.

32. (New) A liquid composition of claim 23 wherein the static contact angle is no more than 20 degrees.